

TRADE INFORMATION GUEZOO7



EXIDE EXTRA

THE BATTERY WITH THAT EXTRA SOMETHING

NOW WITH 36 MONTHS WARRANTY, THAT'S AN EXTRA 12 MONTHS

Advanced Calcium Aq9 technology for high performance and longer life, a real EXTRA bonus. Exide Extra is packed with EXTRA features that deliver real trade and consumer benefits. This premium product is manufactured in Australia in accordance with the latest production methods and quality controls.



- Advanced Calcium Ag9 technology combined with improved design to guarantee LONGER LIFE.
- Modern design featuring recessed terminals for added safety and stackability.
- Eye catching color to distinguish this as a battery above all others.
- Handle for safe, easy transportation and fitting.
- State of Charge Indicator.
- Improved internal design for maximum performance and long life.
- The latest in polyethylene envelope separators to protect against plate shedding vibration and provide longer life.
- Improved cranking and amp hour performance to meet the latest
- Sealed to resist spills and provide maintenance free performance.
- · Wide range of EXIDE EXTRA to suit most popular late
- · Distinctive labelling with Installation tips for the consumer and trade alike.

performance and long life.

LOW MAINTENANCE

A range of lower capacity batteries with proven technology to suit very early model vehicles both imported and manufactured in Australia.

A national 12 Month Warranty is supported by an extensive dealer network.

The EXIDE LOW MAINTENANCE range uses a proven technology combined with the latest battery designs that have provided higher performance than previously achieved.

- Hybrid technology to suit electrical requirements of early
- Modern design featuring recessed terminals for added safety and stackability.



longer life.

· Handle for safe, easy transportation and fitting.

Improved internal design for maximum electrical

The latest in polyethylene envelope separators to

protect against plate shedding vibration and provide

· Positive seal vent plugs, to resist spills and allow topping when required.



EXIDE ENDURANCE PLUS

A range of batteries to fit your latest model vehicles wherever they come from. The latest Calcium technology and some with Ag9 silver alloy as demanded by many new vehicle manufacturers.

A national 24 Months warranty to ensure peace of mind backed by a network of EXIDE dealers around Australia and New Zealand.

EXIDE ENDURANCE PLUS in many cases meets or exceeds the original vehicle electrical specifications of the vehicle manufacturer. In the case of Holden, Ford & Mitsubishi vehicles manufactured in Australia the recommended batteries are the approved replacement products that meet the manufacturers electrical requirements.

With features PLUS, the EXIDE ENDURANCE PLUS will be a high volume product demanded by your customers.

- Advanced Calcium technology some with Ag9 to resist extreme under bonnet temperatures and corrosion delivering
- Modern design featuring recessed terminals for added safety and stackability.
- Handle for safe, easy transportation and fitting.

- Improved internal design for maximum performance and long life.
- The latest in polyethylene envelope separators to protect against plate shedding vibration and provide longer life.
- Improved cranking and amp hour performance to meet the latest vehicle requirements.
- Positive seal vent plugs to resist spills and provide maintenance free performance, can be removed for topping up if required.
- Wide range to suit many popular imported and locally made vehicles.



EXIDE ENDURANCE

A range of batteries with proven technology generally recommended for early model vehicles and some later models. With an average car park life of over 10 years there are many vehicles on the roads in excess of the average. The EXIDE ENDURANCE has the proven technology to suit the electrical requirement of these vehicles.

With a 24 Month National Warranty backed by an extensive dealer network your customers will travel with a real guarantee.

EXIDE ENDURANCE with proven technology comes with many modern features. Hybrid technology to suit electrical requirements of early model vehicles and many later models. Modern design featuring recessed terminals for added safety and stackability.

- Handle for safe, easy transportation and fitting.
- Improved internal design for maximum electrical performance and long life.
- The latest in polyethylene envelope separators to protect against plate shedding vibration and provide longer life.
- Positive seal vent plugs, coloured yellow as a check item, to resist spills and provide maintenance free performance with the ability to allow topping up if required.
- Wide range to suit many popular imported and locally made vehicles.



BATTERY SPECIFICATIONS Volte Ass CCA RC A.H Length Width Height Nom. Wgt Acid Lt. Terminal Type Ass CCA RC A.H Length Width Height Nom. Wgt Acid Lt. Terminal Type

PASSENGER STANDARD WIDTH EXTRA X56C E550HE Sealed MF 12 C 550 105 58 232 173 183 15.5 3.3	Terminal Type	Ledges
EVED VECD FEEDILE COLUMN TO DO SEO 405 FO 000 454 400	SAE POST	S&EL
ESTRA X56D E550HE Sealed MF 12 D 550 105 58 226 171 183 15.5 3.3	SAE POST	NL
ENDURANCE PLUS 54C P460G 12 C 470 90 232 173 183 14.5 3.5	SAE POST	S&EL
ENDURANCE PLUS 54D P460E 12 D 470 90 226 171 183 14.5 3.5	SAE POST	NL
ENDURANCE 53C P460C 12 C 460 85 232 173 185 14.1 3.6	DUAL FIT	S&EL
ENDURANCE 52D P460D 12 D 460 85 232 173 183 14.0 3.6	SAE POST	S&EL
ENDURANCE 52C P460F 12 C 460 85 226 171 185 14.0 3.6	DUAL FIT	NL
LOW MAINTENANCE LM51C N51/N49/LM380C 12 C 400 75 232 173 185 13.6 3.5	DUAL FIT	S&EL
LOW MAINTENANCE LM51D N50/N48/LM380D 12 D 400 75 232 173 183 13.5 3.5	SAE POST	S&EL
LOW MAINTENANCE LM50C N47 12 C 320 60 232 173 185 12.6 3.7	DUAL FIT	S&EL
LOW MAINTENANCE LM50D N46 12 D 320 60 232 173 185 12.5 3.7	SAE POST	S&EL
PASSENGER NARROW WIDTH		
EXTRA X60C E370C Sealed MF 12 C 390 70 40 226 132 223 12.5 2.9	SAE POST	NL
EXTRA X60CP NEW Sealed MF 12 C 370 70 40 226 132 223 12.3 2.9	J.I.S POST	NL
EXTRA X60D E370D Sealed MF 12 D 390 70 40 226 132 223 12.5 2.9	SAE POST	NL
EXTRA X60CD NEW Sealed MF 12 D 370 70 40 226 132 223 12.3 2.9	J.I.S POST	NL
ENDURANCE 43C P310C 12 C 330 60 235 132 200 10.7 2.6	SAE POST	EL
ENDURANCE 43D P310D 12 D 330 60 235 132 200 10.7 2.6	SAE POST	EL
LOW MAINTENANCE LM43C N39 12 270 45 235 132 200 10.7 2.6	SAE	EL
LOW MAINTENANCE LM43D N38 12 270 45 235 132 200 10.7 2.6	SAE	EL
PASSENGER J.I.S.		
EXTRA X40C E360C Sealed MF 12 C 330 60 35 185 132 223 11.5 3.1	SAE POST	NL
EXTRA X40CP NEW Sealed MF 12 C 310 60 35 185 132 223 11.3 3.1	J.I.S POST	NL
EXTRA X40D E360D Sealed MF 12 D 330 60 35 185 132 223 11.5 3.1	SAE POST	NL
EXTRA X40DP NEW Sealed MF 12 D 310 60 35 185 132 223 11.3 3.1	J.I.S POST	NL
ENDURANCE 40C P305BE 12 C 310 55 185 132 223 11.5 3.1	SAE POST	NL
ENDURANCE 40D P305A 12 D 310 55 185 132 223 11.3 3.1	SAE POST	NL
ENDURANCE 40CP P305C 12 C 300 55 185 132 223 11.5 3.1	J.I.S POST	NL
ENDURANCE 40DP P305D 12 D 300 55 185 132 223 11.3 3.1	J.I.S POST	NL
LOW MAINTENANCE LM40C NS40BE 12 C 270 45 185 132 223 9.5 2.5	SAE POST	NL
OTHER PASSENGER		
EXTRA X55D23C 55D23L Sealed MF 12 C 550 105 60 236 173 220 16.5 3.8	SAE POST	S&EL
EXTRA X55D23D 55D23R Sealed MF 12 D 550 105 60 236 173 220 16.5 3.8	SAE POST	S&EL
ENDURANCE PLUS DIN44 37A Sealed MF 12 C 350 54 211 176 175 12.0 2.3	SAE POST	
ENDURANCE PLUS 55H MF55H Sealed MF 12 C 460 85 55 242 175 190 15.5 4.0	SAE POST	S&EL
ENDURANCE PLUS DIN55 PDIN55 Sealed MF 12 C 460 80 245 176 175 14.0 3.3	SAE POST	S&EL
ENDUDANCE BLUE COLL TO THE COL	SAE POST	S&EL
ENDURANCE PLUS 66H MF66H Sealed MF 12 C 600 120 70 277 175 190 17.5 4.5	SAE POST	S&EL
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0	SAE POST	S&EL
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0 ENDURANCE PLUS DIN77 PDIN77 Sealed MF 12 C 650 125 315 175 175 -		
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0 ENDURANCE PLUS DIN77 PDIN77 Sealed MF 12 C 650 125 315 175 175 TS ENDURANCE PLUS DIN88 DIN88 Sealed MF 12 C 650 140 353 176 175 21.5 3,8	SAE POST	S&EL
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0 ENDURANCE PLUS DIN77 PDIN77 Sealed MF 12 C 650 125 315 175 175 T ENDURANCE PLUS DIN88 DIN88 Sealed MF 12 C 650 140 353 176 175 21.5 3,8 ENDURANCE PLUS 55D23C NEW 12 C 460 85 236 173 220 15.5 4.0	SAE POST SAE POST	S&EL S&EL
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0 ENDURANCE PLUS DIN77 PDIN77 Sealed MF 12 C 650 125 315 175 175 ENDURANCE PLUS DIN88 DIN88 Sealed MF 12 C 650 140 353 176 175 21.5 3,8 ENDURANCE PLUS 55D23C NEW 12 C 460 85 236 173 220 15.5 4,0 ENDURANCE PLUS 55D23D NEW 12 D 460 85 236 173 220 15.5 4.0	SAE POST SAE POST SAE POST	S&EL
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0 ENDURANCE PLUS DIN77 PDIN77 Sealed MF 12 C 650 125 315 175 175 T75 ENDURANCE PLUS DIN88 DIN88 Sealed MF 12 C 650 140 353 176 175 21.5 3.8 ENDURANCE PLUS 55D23C NEW 12 C 460 85 236 173 220 15.5 4.0 ENDURANCE PLUS 55D23D NEW 12 D 460 85 236 173 220 15.5 4.0 ENDURANCE PLUS 50D20L 12 C 430 80 202 173 225 13.0 4.0	SAE POST SAE POST SAE POST SAE POST	S&EL S&EL
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0 ENDURANCE PLUS DIN77 PDIN77 Sealed MF 12 C 650 125 315 175 175 T ENDURANCE PLUS DIN88 DIN88 Sealed MF 12 C 650 140 353 176 175 21.5 3.8 ENDURANCE PLUS 55D23C NEW 12 C 460 85 236 173 220 15.5 4.0 ENDURANCE PLUS 55D23D NEW 12 D 460 85 236 173 220 15.5 4.0 ENDURANCE PLUS 50D20L 12 C 430 80 202 173 225 13.0 4.0 ENDURANCE PLUS 50D20R 12 D 430 80 202 173 225 13.0 4.0	SAE POST SAE POST SAE POST SAE POST SAE POST	S&EL S&EL
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0 ENDURANCE PLUS DIN77 PDIN77 Sealed MF 12 C 650 125 315 175 175 T ENDURANCE PLUS DIN88 DIN88 Sealed MF 12 C 650 140 353 176 175 21.5 3.8 ENDURANCE PLUS 55D23C NEW 12 C 460 85 236 173 220 15.5 4.0 ENDURANCE PLUS 55D23D NEW 12 D 460 85 236 173 220 15.5 4.0 ENDURANCE PLUS 50D20L 12 C 430 80 202 173 225 13.0 4.0 ENDURANCE PLUS 50D20R 12 D 430 80 202 173 225 13.0 4.0 ENDURANCE PLUS	SAE POST SAE POST SAE POST SAE POST SAE POST SAE POST	S&EL S&EL
ENDURANCE PLUS DIN66 PDIN66 Sealed MF 12 C 600 110 278 176 175 16.0 4.0 ENDURANCE PLUS DIN77 PDIN77 Sealed MF 12 C 650 125 315 175 175 T ENDURANCE PLUS DIN88 DIN88 Sealed MF 12 C 650 140 353 176 175 21.5 3.8 ENDURANCE PLUS 55D23C NEW 12 C 460 85 236 173 220 15.5 4.0 ENDURANCE PLUS 55D23D NEW 12 D 460 85 236 173 220 15.5 4.0 ENDURANCE PLUS 50D20L 12 C 430 80 202 173 225 13.0 4.0 ENDURANCE PLUS 50D20R 12 D 430 80 202 173 225 13.0 4.0	SAE POST SAE POST SAE POST SAE POST SAE POST	S&EL S&EL

For more information and online ordering call 1800 800 811

or visit our dealernet on www.exide.com.au